

Specification Text

Bird Protection Glass
ISOLAR®
Ornilux® mikado



Product Characteristic

Insulating glass unit with transparent structured UV reflective coating to reduce the risk of bird window strikes. In addition, combined with solar or thermal low-E coating according to technical performance requirements. Successfully tested at the American Bird Conservancy' and/or Fringilla, Rybachy' flight tunnel test.

Insulating glass acc. EN 1279

Ornilux® mikado N34 //

Insulating glass unit (from the outside to inside):

Single glass thickness / - type: (or nominal thickness)	4:	mm
Coating Position	mikado #2 / N34 #3	
Insulating glass unit gap:	16	mm
Single glass thickness / - type: (or nominal thickness)	:44.2	mm

Total thickness of insulated glass unit	28	mm
---	----	----

(total thickness made up by nominal thickness and IGU gap)

Glass thicknesses according to static requirements

Technical values according to EN410/EN673:

The following technical values must at least be specified (vertical installation):

Product name	Ornilux® mikado N34 //
Heat transfer coefficient (Ug):	1.1 W/(m²K) acc. EN 673
Light transmission:	79% acc. EN 410
Light reflection outside:	13% acc. EN 410
Solar Heat Gain (g-value):	60% acc. EN 410
Flight Tunnel Test	77 ABC Tunnel Test

Deviating technical values resulting from other glass thicknesses or glass types shall be communicated to the Contractor.

Amount:

Unitt: sqm

Nov-20